

Multi-Jig Mesh Welding Machine



多模式自動化網焊機



金錒機電廠股份有限公司
GOLDEN SPOT INDUSTRY INC.

NO.13, Ln. 498, Side Rd., Wufeng Dist,
Taichung City, 41356, Taiwan
41356 台中市霧峰區四德路498巷13號

TEL:+886-4-23334589#7(Rep)
FAX:+886-4-23331788
<http://www.goldspot.com.tw>
E-mail:welding@goldspot.com.tw



金錒機電廠股份有限公司
GOLDEN SPOT INDUSTRY INC.

橫線自動下料裝置 Auto Cross Wire Feeder

標配左右各一組移載機構
Standard Accessory : Twin feeder with wire jigs.
可選配一至三組落料系統
Optional for loading system: 1~3 units.
自動下料速度最快 3支/秒
Feeding speed: 3 pcs/sec.

人機介面 Finger-touch Screen (HMI) Operation

以圖文顯示，操作容易
Graphic Design.
User-Friendly.

規格 Specification:

網片尺寸最大 Mesh Max. specs :
24"X48"(610mmX1219mm) X2pcs.
特殊規格，可接受訂製
Other sizes are available.

提昇產能/減少人力 Increase production / Reduce Labor costs.

直向點焊-可一次多點焊接
Vertical way action (Multi-point at once).
人員操作簡易，工序簡化
Reduce wire loading time.
放置少量直線，大量橫線自動下料
Suitable for mesh with large number
of cross wires but few of line wires.

雙系統 Double Welder

雙點焊系統 (標配五支汽缸作業)
Independent Double Welding System.
(Each with 5 pcs welding cylinders.)
雙下拱結構
Dual Lower Arch Structure.
網片獨自作業(以伺服馬達傳動)
Independent control, driven by servo motor.
可單邊操作，或雙邊不同網片作業
Either one side or two sides operation with
different workpiece.

多用途焊接型式 Multi-function Welding method.

三層網-粗細、長短配合焊接
Applicable to Double Wire Mesh with different
wire thickness and length of mesh.
結合網片與配件焊接
Mesh with Accessory welding.
打鬆機構-網片退出模具，成品人工移出
Mesh Releasing Device- Mesh released from the jig,
mesh unloaded manually.



適用 Application:

三層結構網、粗細線、長短線、有框者
Double Wire Mesh, different wire thickness,
various length, wire frame.
如置物架、倉庫籠
EX: Wire Shelves, Wire Cages.